



CAST DUCTILE IRON COUPLINGS STRAIGHT & TRANSITION SELECTION TABLE

For 2", 2-1/2" and 3" Couplings, see 1708 / 1706 (page 1.8.1)


NOM. PIPE SIZE	FIRST END				BY X	SECOND END				MAX. PRESSURE (Working) LBS./IN. ²	NUMBER OF FASTENERS DIA. X LENGTH	SLEEVE LENGTH IN.	SHIPPING WEIGHT***	
	RANGE			END CODE		RANGE			END CODE				LBS.	KG.
	LOW	PIPE OD (Actual)	HIGH*			LOW	PIPE OD (Actual)	HIGH*						
4	3.45	3.50	3.60	F4T	X	3.45	3.50	3.60	F4T	175	4 5/8 x 8	5	17	7.7
	3.75		4.05	F3A		3.75		4.05	F3A					
	4.05		4.35	F3B		4.05		4.35	F3B					
	4.40	4.50	4.60	D3		4.40	4.50	4.60	D3		4 5/8 x 11	7	20	9.0
	4.74	4.80	5.10	A1		4.74	4.80	5.10	A1					
	5.10		5.30	E5		5.10		5.30	E5					
6	5.85	6.00	6.15	F3A	X	5.85	6.00	6.15	F3A	175	5 5/8 x 8	5	25	11.3
	6.15		6.45	F3B		6.15		6.45	F3B					
	6.50	6.63	6.70	D3		6.50	6.63	6.70	D3		5 5/8 x 11	7	33	14.9
	6.86	6.90	7.10	A1		6.86	6.90	7.10	A1					
	7.15		7.35	E5		7.15		7.35	E5					
8	7.90	8.00	8.25	F3A	X	7.90	8.00	8.25	F3A	175	6 5/8 x 8	5	30	13.6
	8.25		8.55	F3B		8.25		8.55	F3B					
	8.55	8.63	8.75	D3		8.55	8.63	8.75	D3		6 5/8 x 11	7	39	17.7
	8.99	9.05	9.30	A1		8.99	9.05	9.30	A1					
	9.30		9.50	E5		9.30		9.50	E5					
10**	9.85	10.00	10.20	F4A	X	9.85	10.00	10.20	F4A	175	7 5/8 x 11	7	59	26.8
	10.20		10.50	F4B		10.20		10.50	F4B					
	10.60	10.75	10.90	D4		10.60	10.75	10.90	D4					
	11.10	11.10	11.40	B2		11.10	11.10	11.40	B2					
	11.55		11.75	A1		11.55		11.75	A1					
	11.90	12.00	12.10	E5		11.90	12.00	12.10	E5					
SERIES 2 (STANDARD STEEL AND DUCTILE SIZES ONLY / PVC DR18)														
10	10.60	10.75	10.90	S9	X	10.60	10.75	10.90	S9	175	7 5/8 x 11	7	49	22.3
	11.10	11.10	11.40	G8		11.10	11.10	11.40	G8					

All dimensions are in inches.

CAST COUPLING CONFIGURATIONS:

- 1406:** Enamel coated Center Sleeve and End Rings, Stainless Steel Fasteners.
- 1408:** Enamel coated Center Sleeve and End Rings, HSLA Steel Fasteners.
- 1506:** Epoxy coated Center Sleeve and End Rings, Stainless Steel Fasteners.
- 1507:** Epoxy coated Center Sleeve and End Rings, HSLA Steel Bolts, complete with Zinc Anodes.
- 1519:** Epoxy coated Center Sleeve and End Plates, HSLA Steel Fasteners, complete with 1/4" Zinc plated cap screw designed for cathodically protected applications.

Note: * The pipe OD or the end plate combination code is used when ordering.
 ** Some transitions may require a stepped center sleeve.
 *** Shipping weights are approximate and vary according to configuration.
 - Recommended torque to 70-80 ft. lbs.



Couplings do not prevent pipe pullout.
 Suitable restraint should be used when required.

ROBAR INDUSTRIES LTD. - BRITISH COLUMBIA
 Phone: (604) 591 - 8811
 Toll Free: (800) 663 - 6553
 Fax: (604) 591 - 5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC
 Phone: (450) 641 - 9525
 Toll Free: (800) 315 - 9525
 Fax: (450) 641 - 4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com



CAST DUCTILE IRON COUPLINGS STRAIGHT & TRANSITION SELECTION TABLE

NOM. PIPE SIZE	FIRST END				BY X	SECOND END				MAX. PRESSURE (Working) LBS./IN. ²	NUMBER OF FASTENERS DIA. X LENGTH	SLEEVE LENGTH IN.	SHIPPING WEIGHT***	
	RANGE			END CODE		RANGE			END CODE				LBS.	KG.
	LOW	PIPE OD (Actual)	HIGH*			LOW	PIPE OD (Actual)	HIGH*						
12**	12.00		12.30	F4A	X	12.00		12.30	F4A	175	8 5/8 x 11	7	74	33.6
	12.30		12.60	F4B		12.30		12.60	F4B					
	12.60	12.75	12.90	D4		12.60	12.75	12.90	D4					
	13.20	13.20	13.60	B2		13.20	13.20	13.60	B2					
	13.80	14.00	14.10	A1		13.80	14.00	14.10	A1					
	14.10		14.35	E5		14.10		14.35	E5					
SERIES 2 (STANDARD STEEL AND DUCTILE SIZES ONLY / PVC DR18)														
12	12.60	12.75	12.90	S9	X	12.60	12.75	12.90	S9	175	8 5/8 x 11	7	55	25.0
	13.20	13.20	13.50	G8		13.20	13.20	13.50	G8					
14	14.60		14.90	F2	X	14.60		14.90	F2	175	9 5/8 x 11	7	100	45.5
	15.30	15.30	15.70	B2		15.30	15.30	15.70	B2					
	15.80	16.00	16.25	A1		15.80	16.00	16.25	A1					
	16.40		16.80	E5		16.40		16.80	E5					
16	17.40	17.40	17.80	B2	X	17.40	17.40	17.80	B2	150	10 5/8 x 11	7	107	48.6
	17.80	18.00	18.20	A1		17.80	18.00	18.20	A1					
	18.40		18.80	E5		18.40		18.80	E5					
18	18.80		19.20	B1	X	18.80		19.20	B1	150	12 5/8 x 11	7	129	58.6
	19.10	19.50	19.70	A2		19.10	19.50	19.70	A2					
	19.70	20.00	20.25	E5		19.70	20.00	20.25	E5					
20	20.80		21.35	B1	X	20.80		21.35	B1	150	12 5/8 x 11	7	140	63.6
	21.35	21.60	21.75	A2		21.35	21.60	21.75	A2					
	21.75	22.00	22.25	E5		21.75	22.00	22.25	E5					
22	22.95		23.35	B1	X	22.95		23.35	B1	150	13 5/8 x 11	7	156	70.9
	23.45		23.85	A2		23.45		23.85	A2					
	23.75	24.00	24.25	E5		23.75	24.00	24.25	E5					
24	25.70	25.80	26.00	A2	X	25.70	25.80	26.00	A2	150	14 5/8 x 14	10	285	129.6
	26.10		26.32	E5		26.10		26.32	E5					

All dimensions are in inches.

HOW TO ORDER:

Determine the product number (1408, etc.) and the pipe OD or end plate combination for each end of the coupling (see page 1.1.1, 1.1.2), and then use the appropriate ordering code as shown in the following example.

To couple a 6" Steel pipe (6.63" OD) to a 6" C900 PVC pipe (6.90" OD), the ordering code is:

1408 - 6.63" x 6.90" i.e. **1408 - 6.63 x 6.90**
 product OD (Actual) OD (Actual) or **1408 - 6D3 x 6A1**
 number

- Note:
- * The pipe OD or the end plate combination code is used when ordering.
 - ** Some transitions may require a stepped center sleeve.
 - *** Shipping weights are approximate and vary according to configuration.
 - Recommended torque to 70-80 ft. lbs.

CAUTION



Couplings do not prevent pipe pullout.
Suitable restraint should be used when required.

ROBAR INDUSTRIES LTD. - BRITISH COLUMBIA

Phone: (604) 591 - 8811
 Toll Free: (800) 663 - 6553
 Fax: (604) 591 - 5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: (450) 641 - 9525
 Toll Free: (800) 315 - 9525
 Fax: (450) 641 - 4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com