

## ROBAR INDUSTRIES LTD.

## SUBMITTAL INFORMATION

## **ROBAR 2406/2506 CAST SERVICE SADDLE**

**USE** Robar 2406/2506 Service Saddles are used to take a service

outlet off a transmission or distibution line.

**MATERIALS** 

Saddle Body Cast Ductile Iron per ASTM A536 standard. Outlet thread are

compliant with AWWA C-800-05

Gasket Gaskets are made from Nitrile Rubber (RBR) compound.

Meets ASTM D2000 standard.

Other materials available on request.

Strap & Fasteners 1/2" NC T-304 Stainless Steel.

1/2" T-304 SS nuts coated with anti-galling compound.

T-304 Stainless Steel strap - 14 gauge.

Coating 2406 - Two coats of red enamel

2506 - Fusion Bonded Epoxy per AWWA C-213 standard.

**PRESSURE** When following Robar installation instructions correctly the

saddle will handle working pressures up to 350 PSI. Contact

Robar for higher working pressures.

SIZES AVAILABLE 2" - 16"

Outlet sizes - 3/4" - 2", "IP" or "CC"

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 604-591-8811 Phone: 450-441-7525
Toll Free: 800-663-6553 Toll Free: 800-315-9525
Fax: 604-591-5288 Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com