



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 5600 SERIES REPAIR CLAMPS

USE

Robar repair clamps are used to effectively repair holes or breaks in water mains. The advantage of a repair clamp is that it allows for a quick repair.

MATERIALS

Shell

T-304 Stainless Steel, fully passivated
Size 2" - 3" - 24 gauge
Size 4" - 30" - 20 gauge

Side bar & Armor

T-304 Stainless Steel, fully passivated

Fasteners

5/8 inch diameter, T-304 Stainless Steel and heavy hex nuts.
Nuts coated with anti-galling compound. Meets AWWA C111 standards.
1/2 inch diameter for model 5606/5696 repair clamps.

Gaskets

Gaskets are made from Nitrile rubber (NBR) compound. Meets ASTM D2000 standard.
Other materials available on request.

PRESSURE

When following Robar installation instructions correctly the repair clamp will handle working pressures up to *150 PSI.
Contact Robar for higher working pressures.

SIZES AVAILABLE

2" - 30" available.
Repair clamp lengths - 6" - 48" long.
Contact Robar for larger nominal sizes and or lengths.

"*" pressure rating is dependant on the condition of the pipe at the time of repair

NOTE: EC Pad available

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com