

ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

AWWA M-11 HARNESS RESTRAINT

<u>USE</u> To restrain flexible couplings being installed on steel

pipelines. The harnesses are supplied in half ring to allow

for easy field welding.

MATERIALS

Restraint Rings Two rings are required. One for each steel pipe on either

side of the coupling. Rings are carbon steel per ASTM

A193.

Tie Rods

Carbon Steel per ASTM A193 Gr B7. Stainless Steel rods

available upon request. Twice as many rods are required.

Coating Supplied bare unless otherwise requested.

PRESSURE Per AWWA M11 manual, working pressures of 50 - 250 PSI

are available. These pressures determine the quantity of

tie rods and diameter of tie rods

SIZES AVAILABLE 14" - 96" for steel pipe. Larger sizes available on request.

Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 604-591-8811 Phone: 450-441-7525
Toll Free: 800-663-6553 Toll Free: 800-315-9525
Fax: 604-591-5288 Fax: 450-441-4894

We bsite: www.robarindustries.com / E-mail: waterworks@robarindustries.com