




5696SC

STAINLESS STEEL SNAP CLAMP



APPLICATIONS

ROBAR 5696SC Single Section SNAP Clamps are used to repair small punctures, pinholes and splits which do not require a full wrap-around gasket.

MATERIAL SPECIFICATIONS

Shell:	T304 Stainless Steel
Sidebar:	T304 Stainless Steel
Gasket:	Nitrile (NBR) Rubber
Fasteners:	T304 Stainless Steel Electrolytic Zinc Plated Nuts Torque is 45ft. lbs
PSI Rating:	150 psi

HOW TO ORDER

Determine the product number (**5696SC**), the pipe outside diameter and the length of clamp you require and then order by using the appropriate ordering code as shown in the following example.

For a 2" steel pipe diameter (2.38") and a length of 6", the ordering code is:

i.e. **5696SC - 2" x 6" Snap Clamp**

5696SC SNAP CLAMP CHART

NOMINAL PIPE SIZE	WORKING RANGE		APPROXIMATE SHIPPING WEIGHT (LBS.)		
			LENGTH OF CLAMP		
	LOW	HIGH	3"	6"	9"
1/2	0.83	0.98	1.0	2.0	3.0
3/4	1.02	1.18	1.0	2.0	3.0
1	1.30	1.46	1.0	2.0	3.0
1-1/4	1.65	1.77	1.0	2.0	3.0
1-1/2	1.89	2.01	1.0	2.5	3.5
2	2.36	2.52	1.0	2.5	4.0
2.5	2.80	2.96	1.0	2.5	4.0
3	3.43	3.66	1.5	3.0	4.5
4	4.41	4.61	1.5	3.0	4.5

All dimensions are in inches.

ROBAR INDUSTRIES LTD.

www.robarindustries.com
waterworks@robarindustries.com

Surrey, British Columbia
Phone: 1-800-663-6553

Saint-Bruno, Quebec
Phone: 1-800-315-9525