



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 7500 SERIES CAST DUCTILE FLANGE COUPLING ADAPTER

<u>USE</u>	Cast Ductile Iron Flange Coupling Adapters are used to flexibly adapt plain end pipe to flanged ends.
<u>MATERIALS</u>	
Flange & Body	The flange and body are Cast Ductile Iron per ASTM A536 standards.
Fasteners	T-bolts and Cross bolts are used. Bolts & Nuts meet AWWA C111 standards. 7504 - High Strength Low Alloy (HSLA) steel bolts and nuts. 7506 - T-304 Stainless Steel and heavy hex nuts. Nuts coated with anti-galling compound.
Coating	Waterarmor G17 Fusion Bonded Thermoplastic per AWWA C229 (Functionally conforms with AWWA C213). NSF/ANSI/CAN 61 approved.
Gaskets	Flange O-Ring gasket - Nitrile (NBR) Coupling gasket Nitrile Butadiene Rubber (NBR). Meets ASTM D2000 standard.
<u>PRESSURE</u>	When following Robar installation instructions correctly the FCA will handle working pressures up to 175 PSI. Contact Robar for higher working pressures.
<u>SIZES AVAILABLE</u>	4" - 12"

Note: Couplings do not prevent pipe pull out

Effective: 06/01/2024

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com